

Richards-Wilcox THERMATITETM



T300-MR & T300 OVERHEAD SECTIONAL INSULATED STEEL DOORS

 Fabricated from pre-painted, hot dipped stucco embossed galvanized steel.



 Insulated with 3" of Neufoam™ polyurethane insulation. CFC and HCFC free.



Sections feature Weatherlock™ thermal break and tongue and groove section joint.



Multi-Ribbed



Ribbed


Unique Multi-Ribbed (MR) Profile

- Multi-Ribbed profile complements contemporary architecture.
- Perfect choice when aesthetics are a key consideration.
- Non-repeating stucco surface texture resists scratches and dirt.

Ribbed Profile

- Recognized as a standard look on many door systems that are already installed.
- RW can provide matching section replacement options to customers quickly and efficiently.

PRODUCT SPECIFICATIONS



SECTION DETAILS

SECTION THICKNESS 3" (76mm)

THERMAL VALUE OF SECTIONS

R 24.52 ft² hF/Btu

FACE SHEET PROFILE Multi-Ribbed / Ribbed

EXTERIOR FACE SHEET THICKNESS

0.019" (0.48mm)

MAXIMUM OPENING WIDTH" 36'-2" (11024mm)

MAXIMUM OPENING HEIGHT 22' (6706mm)

FINISH Two coat, baked-on paint system on exterior side, primer and polyester finish coat.



GLAZING OPTIONS

	M M M		
Type CPL (24"x 8")	Type D (34"x 16")	Type E (24"x 12")	Fullview

WARRANTY

10 years against delamination of the panels 1 year on materials and workmanship

*Thermal Values Calculated. **For larger sizes, please consult factory.

SECTION SCHEDULE

DOOR OPENING HEIGHT	Sections High	DOOR OPENING WIDTH	Max no. of Windows
7'-1" to 8'-1" (2159mm to 2464mm)	4	8'-0" to 9'-2" (2438mm to 2794mm)	2
8'-2" to 10'-1" (2489mm to 3073mm)	5	9'-3" to 12'-2" (2819mm to 3708mm)	3
10'-2" to 12'-1" (3099mm to 3683mm)	6	12'-3" to 16'-2" (3734mm to 4928mm)	4
12'-2" to 14'-1" (3708mm to 4293mm)	7	16'-3" to 19'-2" (4953mm to 5842mm)	5
14'-2" to 16'-1" (4318mm to 4902mm)	8	19'-3" to 24'-2" (5867mm to 7366mm)	6
16'-2" to 18'-1" (4928mm to 5512mm)	9	24'-3" to 28'-2" (7391mm to 8585mm)	7



